EN 2022.11.14 Page 1/2

Platon Flexi Original

Platon Flexi Original is a decoupling membrane with shear force control technology. The matting incorporates a PP dimpled sheet in between a PP fleece backer and PP Mesh surface.

Description:

Platon Flexi Original is a decoupling membrane with shear force control technology. The matting incorporates a PP dimpled sheet in between a PP fleece backer and PP Mesh surface.



Application:

To be used on concrete, screed, OSB, Chipboard, Plywood and for refurbishing older wood or tiled surfaces.

Installation:

To be installed on a prepared floor using tile adhesive. Spread adhesive and use a notched thorwel between 4x4mm and 6x6mm depending on the substrate and adhesive type. Thoroughly embed the matting into the adhesive ensuring full coverage. Allways follow the requirements of the tile adhesive supplier.

Fore more details see laying instruction on our website.

Storage:

To be stored upright with original packaging, in a dry place protected from sunlight

Approvals and guarantee





Platon Flexi Original

Product data	Value	Designation
Thickness	3	mm
Surface	PP Mesh	-
Width	1000	mm
Material	PP	-
Underside	PP Fleece	-
Weight pr. m2	600	g

Product number	Length in mm			
Properties	Method	Unit		Value
Fill volume	-	I/m²	1.2	
Adhesion	EN 1348	N/mm2	0.2	
Crack bridging	-	mm	2	
Robinson Floor Test	ANSI C627	Class	Extra Heavy	



