

# Butyl Tape

## Butyl tape for battens and counter battens

### Description :

The butyl tape consists of polyethylene reinforcement with butyl adhesive on both sides. The adhesive is protected by foil, which is peeled off in two stages when the tape is to be used. The tape is waterproof, strongly adhesive and aging-resistant. The product is dimensionally stable in moisture, and acts as a gasket between counter battens and diffusion-open roofing underlays or between battens and weather barriers. The tape provides a waterproof and secure seal around nails or screws. The tape adheres to timber, diffusion-open underlays and weather barriers with a surface of polypropylene felt etc. The use of butyl tape prevents leaks where nails have been used and contributes to a moisture-proof building.

### Application :

It is used as an accessory for diffusion-open underlays or weather barriers with a surface of polypropylene felt. It is used as a sealing tape between the counter battens and the underlay or between battens and weather barriers.

### Storage :

Isola Butyl Tape should be stored dry and frost-free and should not be exposed to direct sunlight or UV. Storage temperature: +5 to +25 °C.

### Approvals and guarantee



### Installation :

The tape is first attached to the underside of the battens or counter battens. Remove the foil protecting the adhesive on one side of the tape and stick it firmly to the batten or counter batten. Then remove the foil on the other side and stick the batten or counter batten to the underlay or weather barrier. Then fasten the counter batten with nails or screws according to the installation instructions for the underlay or weather barrier.

For more details see laying instruction on our website.

### Accessories for :

Undertak Tyvek Pro 1,30 x 50m  
Tyvek Pro Super  
Isola Tyvek D-Pro 1,50x 50m  
Tyvek Pro Xtra 1,50 x 25 m



# Butyl Tape

Product data	Value	Designation
Product number		Width
564162		50 mm

