EN 2022.11.14 Page 1/2

MEMBRA® Cuff for Wall

Self-adhesive membrane system for wet rooms

Description:

Membra Pipe Gasket Wall is a self-adhesive gasket based on PE foam with a polyester-based collar. The adhesive panel is protected with silicone-treated tear-off foil. The tear-off foil is divided in two for easy and safe installation.



Application:

Membra Pipe Gasket Wall is part of the Membra Wet Room System. The product is used to ensure a robust and waterproof seal with pipe penetrations in walls. The gasket provides excellent adhesion to solid substrates such as wet-room panels, plasterboard, waterproof wood wool boards etc.

Storage:

Membra Pipe Gasket Wall should be stored in a dry and frost-free place and should not be exposed to direct sunlight. Storage temperature: +5 to +25 $^{\circ}\mathrm{C}$

Installation:

Membra Pipe Gasket Wall is installed by passing the gasket over the pipe protruding from the wall. Then remove the protective paper so that the gasket can be glued to the substrate. Use a profiling tool to stick the gasket down firmly. See separate installation instructions.

NB: The substrate must be firm, clean, dry and free from grease. Absorbent surfaces should first be primed with Membra Adhesive Primer.

Fore more details see laying instruction on our website.

Accessories for:

MEMBRA® Membranduk

Approvals and guarantee







MEMBRA® Cuff for Wall

Product data	Value	Designation
Thickness	0,95	mm
Material	PE foam	-

Product number	Diameter
620501	9-16 mm
620502	17-25 mm
620503	28-35 mm
620506	100-110 mm
620505	75-90 mm
620504	46-55 mm



