

Veggpapp

Windproofing in exterior walls, roofs and floors

Description :

Isola Sheathing Felt consists of cellulose board impregnated with asphalt. The felt is waterproof, windproof and diffusion-open, but has relatively high vapour resistance. Isola Sheathing Felt is supplied in widths that are suitable for the standard stud distance of c/c 600 mm, and in widths that are intended for windproofing joints in GU plaster and asphalt windproof boards.



Application :

Used as a wind barrier on the cold side of the insulation in exterior walls, roofs and floors.

Installation :

Fitted directly to the stud/framework. The joints are overlapped over the studs and sills and clamped against them with battens to achieve an airtight construction.

For more details see laying instruction on our website.

Storage :

The product should be stored in a dry place and not exposed to direct sunlight.

Approvals and guarantee



Veggpapp

Product data	Value	Designation
Material	Cellulosepapp impregnert med bitumen	-
Weight pr. m2	450	g

Product number	Width	Length in mm
535067	670 mm	30000 mm
535125	1250 mm	16000 mm

Properties	Method	Unit	Value
Euro fire class according to EN 13501-1	EN ISO 11925-2	-	F
Resistance to water penetration	EN 1928 (A)	-	W1
Water vapour resistance (sd)	EN ISO 12572 (C)	m	0,29
Tear resistance MD	EN 12311-1	N	>15
Tear resistance CMD	EN 12311-1	N	>15
Pliability	EN 1109	°C	≤15
Water tightness after artificial ageing	EN 1928 (A)	-	W2

